

HOLDER

NO COMPROMISES



HOLDER C 345

TECHNICAL DATA HOLDER C 345

Characteristics	Engine	4-stroke diesel
	Power output	31 kW (42 HP)
	Cylinders	4
	Cooling	Water cooling
	Air filter	Dry air filter
	Tank capacity	40 l
	Drive	hydrostatic four-wheel drive, controlled with digital electronics
	Differential lock	Front and rear, simultaneously electronically switchable, easy to operate with the toggle switch, 100% effective for both axles
	Max. speed	36 km/h
	Power take-offs	load-dependent, independent engine power take-off, front/rear
	Brakes	hydraulically activated drum brakes/mechanical handbrake
	Steering	Full hydrostatic articulated-frame steering (load-sensing)
	Hydraulic system/pump	8,09 ccm/U, 24 l/min
	Hydraulic oil quantity	16 l
Dimensions	Excavation power, front/rear	800 kg/800 kg, KAT IN und KAT I
	Auxiliary control valves	Extensive expansion possibilities designed for the respective usage
	Activated carbon filter and air conditioning	optional
	Empty weight	1.390 - 1.790 kg
	Gross vehicle weight	3.000 kg
	Gross axle weight rating, front/rear	1.800 kg
	Coupling load	600 kg
	Wheel base	1.700 mm
	Total length with rear three-point hitch	3.625 mm
	Total height with cabin²	2.000 - 2.040 mm
Track²	968 mm	
Smallest total width²	1.296 mm	
Load area/platform dimensions	1.160 x 1.110 x 200 mm	

¹ incl. driver with 75 kg, depending upon tyres and equipment ² depending upon tyres

FOUR SEASONS, ONE HOLDER

You have the entire portfolio of attachments for year round use at your disposal. Whether sweeping, mowing, suction extraction or clearing, the C 345 is the perfect vehicle for all purposes. The attachments can be changed easily, without tools and safely by a single person. Load-dependent power take-offs with adjustable rotational speeds ensure an enormously high degree of effectiveness with their direct power transmission from the motor to the attachments. Performance hydraulics of up to 75 litres are available.



FOR ECONOMIC EFFICIENCY THROUGHOUT THE YEAR

STANDARD HOLDER ADVANTAGES



Versatility



Articulated-frame steering



Real four-wheel drive



Wheel load balance



Four wheels of equal size

ROOM FOR TWO

Compact strength, but still enough room for two people; that's the Holder C 345. The municipal equipment carrier with articulated-frame steering is equipped with all Holder advantages and convinces particularly with a slim vehicle width. Not only on sidewalks is it the optimal equipment for sweeping and snow removal work.

The continuous hydrostatic four-wheel drive through 4 single wheel motors on four equal sized wheels results in high tractive and thrust forces, optimal traction and soil conservation even in curves as a result. With 42 HP and stepless speed control, the C 345 offers optimal usage possibilities.

Optimal consultation, sales and service from your Holder partner:

Max Holder GmbH
Max-Holder-Straße 1
72555 Metzingen
Germany

Telephone: +49 7123 966-0
Fax: +49 7123 966-213

info@max-holder.com
www.max-holder.com