



**HOLDER**

**HOLDER X 45 / X 45i**





## TECHNICAL DATA

|   | Petrol: X 45i   | Diesel: X 45                   |
|---|---|--------------------------------|
| <b>ENGINE</b>                               | Kubota 4 cylinder petrol  | Kubota 4 cylinder turbo diesel |
| <b>Displacement</b>                         | 1605 cm <sup>3</sup>  | 1498 cm <sup>3</sup>           |
| <b>Power</b>                                | 32,6 kW (44 HP)   | 31 kW (42 HP)                  |
| <b>Rated speed</b>                          | 2600 rpm  | 2800 rpm                       |
| <b>Cooling</b>                              | Water cooling   |                                |
| <b>Fuel tank capacity</b>                   | 42 l  |                                |
| <b>DRIVE</b>                                | Hydrostatic traction drive, stepless road speed control, four wheels of the same size   |                                |
| <b>Maximum speed</b>                        | 27 km/h   |                                |
| <b>Brakes</b>                               | Hydrostatic brake on the front axle, acts on all four wheels, mechanical parking brake on the front axle with two drum brakes |                                |
| <b>HYDRAULICS</b>                           | 1. circuit 55 l/min at 2600 rpm,<br>2. circuit 30 l/min at 2600 rpm,<br>3. circuit 5 l/min at 2600 rpm                        |                                |
| <b>Hydraulic oil quantity</b>               | 15 l  |                                |
| <b>Lifting capacity</b>                     | Front 750 kg  |                                |
| <b>WEIGHT</b>                               | Including driver at 75 kg, depending on tyres and equipment   |                                |
| <b>Tare weight</b>                          | 1280 kg   |                                |
| <b>Permissible gross weight</b>             | 2300 kg   |                                |
| <b>Permissible axle load</b>                | Front 1190 kg / rear 1190 kg  |                                |
| <b>Tow-bar load on the trailer coupling</b> | 75 kg   |                                |
| <b>Towing capacity</b>                      | Braked 900 kg   |                                |
| <b>Maximum payload</b>                      | 1020 kg   |                                |
| <b>DIMENSIONS</b>                           | Tyres 23 x 10,50-12   |                                |
| <b>Wheelbase</b>                            | 1360 mm   |                                |
| <b>Total length</b>                         | 2870 – 2905 mm  |                                |
| <b>Total height with cab</b>                | 1960 – 2020 mm  |                                |
| <b>Total outside width</b>                  | 1094 mm   |                                |
| <b>Turning circle</b>                       | 2150 mm   |                                |
| <b>SWEeper-SUCTION-UNIT</b>                 |   |                                |
| <b>Hopper, gross / net</b>                  | 1 m <sup>3</sup> / 0,7 m <sup>3</sup>   |                                |
| <b>Fresh water tank</b>                     | 150 l   |                                |
| <b>Max. sweeping width</b>                  | 2050 mm   |                                |

### PERFECTLY MATCHED ATTACHMENTS FOR FOUR SEASON USE

- X<sup>3</sup> hopper for sweeping, mowing, watering and washing
- Plattform
- Setting-down device
- 2-brush system with individual brush control
- Front sweeping brush
- Front rotary mower with optional mulching kit
- Front washing bar
- Side-clearing plough
- Vario snow plough
- Roller spreader
- Disc spreader

### YOU ARE IN GOOD HANDS

- Up to 36 month warranty
- Reliable spare parts supply
- close service network and local partners
- Long operational life span
- High stability of value
- Rental, financing and leasing

### COMFORTABLE CABIN

- Rear view cam
- Suction mouth cam
- Hands-free-device for mobile phone
- Panoramic cab
- High class seat with 3-point-belt



### YOUR TOP BENEFITS

- Strongest in it's class with 42 HP and 44 HP
- Comfortable driver's cabin
- Intuitive and ergonomic working joystick
- 3 applications with only one hopper
- Low-noise sweeping
- Made for low height car parks
- High ramp angle for passing obstacles and higher curbs

**HOLDER IN ACTION: [www.youtube.com/user/maxholdergmbh](http://www.youtube.com/user/maxholdergmbh)**

**HOLDER**  
NO COMPROMISE

**Max Holder GmbH**  
Mahdenstraße 8 | 72768 Reutlingen | Germany  
Phone: +49 7121 930729-0 | Fax +49 7121 930729-213  
info@max-holder.com | [www.max-holder.com](http://www.max-holder.com)